PerformancePro
PROUDLY BUILT IN THE USA SINCE 2000 PUMPS


PerformancePro Pumps Engineering Data Packet


Pump:


Series:	A2 Low Speed
Pump Model:	A2-1/8-39
Design:	Self Priming
Inlet:	2 inch
outlet:	2 inch
Impeller:	A1H
Trim:	4.35
Fluid:	Water


Motor:


Motor Number:	APM-342
Manufacturer:	Baldor
Rated HP:	0.13
Total HP:	0.18
Speed:	1725
Enclosure:	TEFC
Frame:	56Y (Square Flange)
Volts:	115/230
Phase:	1
Frequency:	60
Amps At Total HP:	2/1












PerformancePro PROUDLY BUILT IN THE USA SINCE 2000 PUMPS	Artesian 2 Low Speed			
	THP: 0.17HP THRU 0.45HP			
Greg Gent	1:7	3/24/21	A2T001123	

34LYM104



34LYM104

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.


REV. DESC: RPL 34EP3501A03 W/34EP3501A16		
REV. LTR: C	VERSION: 03	TDR: 000000926896
FILE: \AAA\00195\548	REVISED: 02:38:16 05/26/2015	BY: ENERINO
MTL: –		

BALDOR

VER 34LC TEFC 56YZ LG KOBX POOL PUMP MTR, BELLEVILLES

SH 1 of 1

CD1210



	LINE A	LINE B	JOIN	JOIN
HIGH	1	4	2,3	J
LOW	1,3	4	2,J	–

NOTES:

1. CONNECTIONS ARE SHOWN FOR CCW ROTATION FACING END OPPOSITE SHAFT EXTENSION (STD). FOR CW ROTATION, INTERCHANGE 5 AND 8 INTERNALLY.
2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD1210

REV. DESC: REMOVE OPTIONAL THERMAL CONNECTION			BALDOR ELECTRIC Co.
REV. LTR: B	VERSION: 01	TDR: 000000373051	
CD1210	FILE: \AAA\00043\115	REVISED: 17:25:25 09/12/2005	TYPE LC, DV, FIX, THERMAL, 5 LEAD
	MTL: –	BY: ENJOEPO	