PerformancePro
PROUDLY BUILT IN THE USA SINCE 2000 PUMPS


PerformancePro Pumps Engineering Data Packet


Pump:


Series:	AP High Head
Pump Model:	AP-5-HH
Design:	Self Priming
Inlet:	3 inch
outlet:	3 inch
Impeller:	AP1/2L
Trim:	5.00
Fluid:	Water


Motor:


Motor Number:	APM-129A
Manufacturer:	Century Motor
Rated HP:	5.00
Total HP:	5.00
Speed:	3450
Enclosure:	ODP
Frame:	56Y (Square Flange)
Volts:	208-230
Phase:	1
Frequency:	60
Amps At Total HP:	21-19.4












PerformancePro PROUDLY BUILT IN THE USA SINCE 2000 PUMPS	Artesian Pro High Speed			
	THP: 3.6HP THRU 5HP			
Greg Gent	1:7	6/13/22	A3D001499	01

Uncontrolled Copy



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 193410 CUST PN: B1000 HP: 5.0 SF: 1.0 ROT: CCWPE RPM: 3450 TYPE: CX CODE: G FORM: FRAME: Y 56 Y VOLTS: 208-230 AMPS: 21.0-19 4 MAX AMPS: SF AMPS: - PH: 1 HZ: 60 INS: B AMB: 40°C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED	B L1 LINE WHITE L2 LINE A NON-REVERSIBLE 17050319	1. SHAFT RUNOUT NOT TO EXCEED .002[.05] T.I.R. 2. FOR THREADED SHAFT EXT. MATING PARTS SHOULD BE RELIEVED ONE THREAD TO CLEAR FILLET. 3. END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST. 4. ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS. 5. FINISH PAINT TO BE BLACK. 6. CTQ REQUIREMENT SEE EP000105-008 7. RoHS & REACH REQUIREMENT SEE EP000014_5.1

PERFORMANCE CURVE		APPROVED SAMPLE	
16365912			
UL COMPONENT		CSA	
FILE#	CCN#	FILE#	GUIDE#
E14663	XZWR2	LR4642	4211-01
CUSTOMER	DISTRIBUTION		

CRITICAL TO QUALITY CHARACTERISTICS(CTQs)
(P) PROCESS
(E) ENGINEERING
(A) APPLICATION
(R) REGULATORY
(L) LIFE

DRAWING REVISION	REVISION BY	DATE
H	RULIAN	03-10-2021
ECO	APPROVED BY	DATE
NMR-0207545	JANE.WU	03-10-2021
ECO DESCRIPTION		
SEE ENMR		

COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED.
PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. AND CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION OF PHYSICAL CONFORMANCE OR STATUTE FOR PROVIDING IT IN DISCLOSE, BY RECEIVING IT, TO ANYONE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY REGAL. THIS DOCUMENT SHALL BE RETURNED TO REGAL UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.

TOLERANCES UNLESS OTHERWISE SPECIFIED			
DEC.	INCH	mm	ANGLE
.X	±0.1	[±.3]	±0.5°
.XX	±0.02	[±0.5]	
.XXX	±0.005	[±0.13]	
.XXXX	±0.0005	[±0.013]	

REMOVE BURRS & BREAK SHARP EDGES .003/.015 [.08.38]
CORNER FILLETS .02 [.5]
MACHINED SURFACES 125 INCH / 3.2 mm
mm SHOWN IN [BRACKETS]

DRAWN BY: H. MARTINEZ
DATE: 01-29-2010
APPROVED BY: D. WENDLING
DATE: 01-29-2010
REFERENCE: -
THIRD ANGLE PROJECTION

Regal Beloit America, Inc.

DESCRIPTION: OUTLINE -
MATERIAL: - PROCESS/FINISH: -
SIZE: C DWG NO: B1000 SHEET: 1

EXTERNAL CONNECTION DIAGRAM

